



- NOTES:**
1. MATERIAL: COPPER ALLOY
 2. PLATING:
 - ITEM 1: 30µm HARD GOLD over min. 50µm NICKEL
 - ITEM 2: GOLD FLASH over NICKEL
 - ITEM 3: NICKEL PLATED
 3. CRIMPING: USE CRIMP TOOL 360X10409X
WITH TOOL INSERT 360X20029X
SELECTOR SETTINGS: 5 FOR AWG 12
4 FOR AWG 14

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

finish: see notes				tolerance ISO 2768-m		dim. in mm	
				date	name		
				drawn	23.03.98	Barcinski	
				appd.	23.03.98	Mickenbecker	
				norm			
				d-old			
3 x b	Ä3554	19.01.11	K.H.	CONEC ®			
a	Origin						
rev.	description	date	name				

scale: 5:1	
material: see notes	
title: HIGH POWER CONTACT FEMALE CRIMP VERSION 20A D-SUB COMBINATION	
dwg no: Inventor 10	DIN-A4
13K11E8A	
part no: 132C11029X	sh: 1