

# Flush-type connector - SACC-DSI-M8MS-8CON-M8-L180 SH - 1424236

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Sensor/actuator flush-type plug-in connector, plug, 8-pos., M8, rear/screw mounting with M8 fastening thread, with straight solder connection



## Key commercial data

Packing unit	0
Minimum order quantity	1
GTIN	 4 046356 712484
Custom tariff number	85366990
Country of origin	GERMANY

## Technical data

### General data

Rated current at 40°C	1.5 A
Rated voltage	30 V
Number of positions	8
Volume resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ

### General characteristics

Standards/regulations	M8 plug-in connector IEC 61076-2-104
Surge voltage category	II
Pollution degree	3
Degree of protection	IP67
Contact material	Cu alloy
Contact surface material	Au
Contact carrier material	PA 66
Material, knurls	Zinc die-cast, nickel-plated
Mounting type	Rear mounting M8 x 1 With flat nut
Connection method	Solder pins

# Flush-type connector - SACC-DSI-M8MS-8CON-M8-L180 SH - 1424236

## Technical data

### General characteristics

Status display	No
----------------	----

## Classifications

### ETIM

ETIM 3.0	EC002061
ETIM 4.0	EC002635
ETIM 5.0	EC002635

### UNSPSC


UNSPSC 11	31251501
UNSPSC 12.01	31251501
UNSPSC 13.2	31251501
UNSPSC 6.01	31251501
UNSPSC 7.0901	31251501

### eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27260701
eCl@ss 5.1	27143423
eCl@ss 6.0	27143423
eCl@ss 7.0	27449001

## Drawings


### Schematic diagram



M8 plug pin assignment, 8-pos., view of pin side

# Flush-type connector - SACC-DSI-M8MS-8CON-M8-L180 SH - 1424236

Drilling diagram



# Flush-type connector - SACC-DSI-M8MS-8CON-M8-L180 SH - 1424236

Dimensioned drawing

