



- 1. PIN: 0.00076[.000030] MINIMUM GOLD IN CONTACT AREA, 0.00381[.000150] MINIMUM TIN ON SOLDER TAILS, ALL OVER 0.00127[.000050] MINIMUM NICKEL
- 2. CUSTOMER TO PROVIDE CARD GUIDANCE SYSTEM
- 3. DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER
- 4. CONNECTOR REQUIRES USE OF 2 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD
- 5. ASSEMBLY KEYED FOR 5 VOLT CARDS
- 6. ASSEMBLY KEYED FOR LOW VOLT CARDS (3.3v)
- 7. MATERIAL: HOUSING & ORGANIZER: LCP, COLOR: BLACK; PIN: BRASS; HOLD-DOWN: PHOSPHOR BRONZE
- 8. HOLD-DOWN: TIN PLATED

6	1,17,34	ALL OTHER PINS	36,67	5535660-2
	35,51,68	OTHER PINS	36,67	5535660-1
5	1,17,34	ALL OTHER PINS	36,67	5535660-1
	35,51,68	OTHER PINS	36,67	5535660-1
VOLTAGE KEYING & IDENTIFICATION		5.0 [1.97]	4.25 [1.67]	3.5 [1.38]
"L" (PIN LENGTH) AND LOCATION				

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L VARELA - DOCKS 03-28-05	Tyco Electronics Corporation Harrisburg, PA 17105-3608
DIMENSIONS: mm [INCHES]		CHK D.L. GORENC 03-28-05	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. WALMSLEY 03-28-05	PIN HEADER ASSY, 68 POSN, RAISED HT, TOP BD MTG, THRU-HOLE, WITH HOLD-DOWNS, AMP MEMORY CARD
0 PLC ±		NAME	
1 PLC ±		PRODUCT SPEC	SIZE CAE CODE DRAWING NO RESTRICTED TO
2 PLC ±		APPLICATION SPEC	
3 PLC ±		WEIGHT 8.5 GRAMS	A1 00779 C=5535660
4 PLC ±		CUSTOMER DRAWING	
ANGLES ±		SCALE 4:1	SHEET 1 OF 1
FINISH		REV 0	

**COPYRIGHT 2005
 TYCO ELECTRONICS CORP
 ALL RIGHTS RESERVED**