



(0.50 mm) .0197"

BSH SERIES

BASIC BLADE & BEAM SOCKET

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?BSH

Insulator Material: Black LCP
Contact Material: Phosphor Bronze
Plating: Au or Sn over 50 μ" (1.27 μm) Ni
Current Rating: 2 A per pin (1 pin powered per row)
Flammability Rating: UL 94 VO
Operating Temp Range: -55 °C to +125 °C
Voltage Rating: 275 VAC
Max Cycles: 100
RoHS Compliant: Yes

PROCESSING

Lead-Free Solderable: Yes
SMT Lead Coplanarity: (0.10 mm) .004" max (030-090) (0.15 mm) .006" max (120-150)
Board Stacking: For applications requiring more than two connectors per board or 90 positions or higher, contact ipg@samtec.com

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



MATED HEIGHT

LEAD STYLE	MATED HEIGHT*
-01	(5.00) .197

*Processing conditions will affect mated height.

ALSO AVAILABLE (MOQ Required)

- 30 μ" (0.76 μm) Gold
- Edge Mount Capability
- 8 mm, 11 mm, 16 mm, 19 mm and 22 mm Stack Height (Caution: Some automatic placement/inspection machines may have component height restrictions. Please consult machinery specifications.) (11 mm, 16 mm, 19 mm and 22 mm not available with 50 positions)

Contact Samtec.

Note: Some lengths, styles and options are non-standard, non-returnable.

BSH	NO. OF POSITIONS PER ROW	01	PLATING OPTION	D	A	OTHER OPTION
Mates with: BTH		<p>-030, -050, -060, -090, -120, -150</p>			<p>-F = Gold Flash on contact, Matte Tin on tail</p> <p>-L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail</p> <p>-C* = Electro-Polished Selective 50 μ" (1.27 μm) min Au over 150 μ" (3.81 μm) Ni on Signal Pins in contact area, Matte Tin over 50 μ" (1.27 μm) min Ni on all solder tails</p> <p>-TR = Tape & Reel (120 positions maximum)</p>	
		<p>*Note: -C Plating passes 10 year MFG testing</p>				
		<p>AGILENT LOGIC ANALYZER TEST POINT CONNECTOR Specify: ASP-65067-01</p>				

BSH	NO. OF POSITIONS PER ROW	01	PLATING OPTION	D	RA	WT	OTHER OPTION
Mates with: BTH		<p>-030, -060, -090</p>			<p>-F = Gold Flash on contact, Matte Tin on tail</p> <p>-L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail</p>		<p>-GP = Guide Post</p>
		<p>WWW.SAMTEC.COM</p>					