

DIMENSIONS D Е F G 0.315 0.618 0.496 0.429 8.00 15.70 12.60 10.90 0.315 0.933 0.496 0.429 8.00 23.70 12.60 10.90 0.315 1.496 0.496 0.429 8.00 38.00 12.60 10.90 0.315 2.142 0.496 0.429 8.00 54.40 12.60 10.90 0.425 2.039 0.602 0.535 10.80 51.80 15.30 13.60

> 170-YYY-27YL000 01 = .098" CLINCH NUT (BOARD SIDE) 02 = .236" CLINCH NUT (BOARD SIDE)

CONTACTS: BRASS - GOLD PLATED

ELECTRICAL:

CURRENT RATING: 5 AMPS CONTACT RESISTANCE: 15 mOhms Max. INSULATION RESISTANCE: 1.000 MOhms min. **VOLTAGE: 500VAC FOR 1 MINUTE** TEMPERATURE: -50° C TO 125° C

RoHS COMPLIANT

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE

BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

NorComp

DRAWN: DATE: 08-18-98 **PAM JENKINS** CHECKED: DATE:

SCALE: SHEET OF REV 2 8

DWG NO.


170-YYY-27YL000

DESCRIPTION: CLINCH NUT HARDWARE


TOLERANCE: ALL DIMENSIONS ARE ±0.010

ALL CLINCH-NUTS ARE 4-40 INTERNAL THREADS


01X 0.065" (BOARD SIDE) - CN1



02X 0.236" (BOARD SIDE) - CN2



03X..... 0.236" (MATING SIDE) - CN8



DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

NorComp

_					
	DRAWN:		DATE:		
	C. SMITH		03-08-06		
	CHECKED:		DATE:		
	SCALE:	SHEET	OF		REV
	FULL		2	2	8

DWG NO. 170-YYY-17YL000

RoHS COMPLIANT