

Fiber optic coupling - FL MM PATCH COUPLER LC-LC - 2700312

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupling, LC/LC, can be used for multi-mode glass fibers

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	20.0 GRM
Custom tariff number	85367000
Country of origin	Switzerland

Technical data

Mechanical characteristics

Number of positions	2
Number of slots	1
Connection profile	LC
Fiber type	Multi-mode fiberglass
Fiber	50/125 µm
Number of fibers	2
Insertion/withdrawal cycles	≥ 500
Connection method	Coupling

Ambient conditions

Ambient temperature (operation)	-25 °C ... 70 °C
Degree of protection	IP20

Material data

Inflammability class according to UL 94	V0
Housing material	PBT
Ferrule material	Zirconia ceramics
Ferrule holder color	White

Fiber optic coupling - FL MM PATCH COUPLER LC-LC - 2700312

Classifications

eCl@ss

eCl@ss 4.0	272607XX
eCl@ss 4.1	27260701
eCl@ss 5.0	19030109
eCl@ss 5.1	19030109
eCl@ss 6.0	19170101
eCl@ss 7.0	19170101
eCl@ss 8.0	19170116

ETIM

ETIM 3.0	EC000515
ETIM 4.0	EC000515
ETIM 5.0	EC000752

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	39121311