

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20  
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
A		INITIAL RELEASE	25SEP2015	N.P X.X
A1		ECR-16-016026	14NOV2016	N.P X.X

TECHNICAL DATA	T411051X02X-000	T411051X03X-000	T411051X04X-000	T411051X05X-000
RATED VOLTAGE	250V	250V	250V	60V
RATED CURRENT	4A	4A	4A	4A
POLLUTION DEGREE	3	3	3	3
OVERVOLTAGE CATEGORY	II	II	II	II
MATERIAL GROUP	II	II	II	II
CONTACT RESISTANCE	≤8mΩ	≤8mΩ	≤8mΩ	≤8mΩ
INSULATION RESISTANCE	>100MΩ	>100MΩ	>100MΩ	>100MΩ
DEGREE OF PROTECTION	IP67	IP67	IP67	IP67
OPERATION TEMPERATURE	-40~85°C	-40~85°C	-40~85°C	-40~85°C

NOTE:

- MATERIAL:
  - ITEM NO.1: NUT -BRASS
  - ITEM NO.2: HOUSING -PA
  - ITEM NO.3: CONTACT -BRONZE
  - ITEM NO.4: HOUSING BODY: BRASS
- CONTACT FINISH: GOLD OVER NICKEL OR SILVER OVER NICKEL
- CABLE WIRES:
  - 18AWG/0.75mm<sup>2</sup> Max. FOR 2-5 PINS
  - 20AWG/0.50mm<sup>2</sup> Max. FOR 8 PINS
- ALL DIMENSIONS ARE FOR NOMINAL REFERENCE ONLY UNLESS OTHERWISE STATED
- PACKAGEING: 1PIECE IN A BAG
- PN INFORMATION

PIN ARRANGEMENT  
D-CODE

T411051X02X-000	T411051X03X-000	T411051X04X-000
-----------------	-----------------	-----------------

T411051X05X-000
-----------------

T4110512051-000	RPC-M12D-FS-5CON-PG9-SHU
T4110511051-000	RPC-M12D-FS-5CON-PG7-SHU
T4110512052-000	RPC-M12D-FS-5CON-PG9-SH
T4110511052-000	RPC-M12D-FS-5CON-PG7-SH
T4110512041-000	RPC-M12D-FS-4CON-PG9-SHU
T4110511041-000	RPC-M12D-FS-4CON-PG7-SHU
T4110512042-000	RPC-M12D-FS-4CON-PG9-SH
T4110511042-000	RPC-M12D-FS-4CON-PG7-SH
T4110512031-000	RPC-M12D-FS-3CON-PG9-SHU
T4110411031-000	RPC-M12D-FS-3CON-PG7-SHU
T4110512032-000	RPC-M12D-FS-3CON-PG9-SH
T4110511032-000	RPC-M12D-FS-3CON-PG7-SH
T4110512021-000	RPC-M12D-FS-2CON-PG9-SHU
T4110511021-000	RPC-M12D-FS-2CON-PG7-SHU
T4110512022-000	RPC-M12D-FS-2CON-PG9-SH
T4110511022-000	RPC-M12D-FS-2CON-PG7-SH
TE PN	TYPE

T411051XXXX-000

CONTACT FINISH:  
 1: GOLD OVER NICKEL  
 2: SILVER OVER NICKEL

NUMBERS OF PINS:  
 02: 2 PINS  
 03: 3PINS  
 04: 4 PINS  
 05: 5PINS  
 08: 8 PINS

CABLE OUTLET:  
 1: PG7(CABLE FEED: 4-6mm)  
 2: PG9(CABLE FEED: 6-8mm)

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN Nick Pan 24AUG2015		CHK Kobby Zhao 24AUG2015		APVD Xiang Xu 24AUG2015		NAME	
mm		0 PLC	±	PRODUCT SPEC	108-106140	M12 FEMALE, D CODE, STRAIGHT SHIELDED CONNECTOR SCREW TERMINAL		SIZE	A2	CAGE CODE	-
		1 PLC	±0.25	APPLICATION SPEC	114-137144	DRAWING NO		RESTRICTED TO	-		
		2 PLC	±0.15	WEIGHT	-	G-T411051XXXX000		SCALE	1:1	SHEET	1 OF 1
		3 PLC	±	CUSTOMER DRAWING	-			REV	A1		
		4 PLC	±								
		ANGLES	±								
		FINISH	-								

1471-9 (3/13)