Plating Wire Size Wire Type Wire Strip Le Stud Size UL Listed Wire Connector  UL Temperate Rating C.S.A Certifit Wire Connector  Panduit Coon Barrel Panduit Die on Barrel Alternate In	fire ature fied ector	Electro-Tin  8 AWG  Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concent  5/8 in.  1/4 in.  Yes, for applications up to 35k Consult cable manufacturer for voltage stress relief instruction with applications greater than 2000 volts.  90° C  Yes  RED	v. or ss .25±.04	00±.02	.37 R Ref  PANDUIT  RED DIE P21  .27±.02 DIA (2) PLS  Beveled wire entry .27±.01 .18±.01
Wire Type  Wire Strip Le Stud Size  UL Listed Wire Connector  UL Temperar Rating  C.S.A Certifit Wire Conne Panduit Colon Barrel  Panduit Die on Barrel  Alternate In	fire ature fied ector	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concent  5/8 in.  1/4 in.  Yes, for applications up to 35k Consult cable manufacturer for voltage stress relief instruction with applications greater than 2000 volts.  90° C  Yes	v. or .25±.04	8 STR	PANDUIT RED DIE P21  .27±.02 DIA (2) PLS  Color coded barrel marking  .27±.01  .18±.01
Wire Strip Les Stud Size UL Listed Wire Connector  UL Temperar Rating  C.S.A Certifit Wire Conne Panduit Colon Barrel  Panduit Die on Barrel  Alternate In	fire ature fied ector	Compact, Compressed or Concentric, Class C: Concent  5/8 in.  1/4 in.  Yes, for applications up to 35k Consult cable manufacturer for voltage stress relief instruction with applications greater than 2000 volts.  90° C  Yes	v. or .25±.04	8 STR	27±.02 DIA (2) PLS  Color coded barrel marking  .27±.01 .18±.01
Stud Size  UL Listed Will Connector  UL Tempera Rating  C.S.A Certifit Wire Connector  Panduit Colon Barrel  Panduit Die on Barrel  Alternate In	fire ature fied ector	1/4 in.  Yes, for applications up to 35k Consult cable manufacturer for voltage stress relief instruction with applications greater than 2000 volts.  90° C  Yes	v. or .25±.04	∞	Beveled wire entry  .27±.01  .18±.01
UL Listed Wi Connector  UL Tempera Rating  C.S.A Certifi Wire Conne  Panduit Colon Barrel  Panduit Die on Barrel  Alternate In	ature fied ector	Yes, for applications up to 35k Consult cable manufacturer for voltage stress relief instruction with applications greater than 2000 volts.  90° C  Yes	or .25±.04	1.00±.02 -	Beveled wire entry  .27±.01  .18±.01
UL Tempera Rating  C.S.A Certifi Wire Conne  Panduit Colon Barrel  Panduit Die on Barrel  Alternate In	ature fied ector	Consult cable manufacturer for voltage stress relief instruction with applications greater than 2000 volts.  90° C  Yes	or .25±.04	——— 1.00±.02 -	Beveled wire entry  .27±.01  .18±.01
Rating  C.S.A Certifi Wire Conne  Panduit Colon Barrel  Panduit Die on Barrel  Alternate In	fied ector	Yes			.18±.01
Panduit Colon Barrel Panduit Die on Barrel Alternate In	ector				
on Barrel Panduit Die on Barrel Alternate In	olor Co	de RED			.56±.04
on Barrel Alternate In			1		
Alternate In	e Index	No. P21		Wire inspection v	window .73 REF
Die Index N on Barrel	ndustry No. ()	N/A	<u> </u>		45°±5°
	CERT	_	.07±.01	2.19	9 REF
	9211.1	Wire Connector			
					CORP. TINLEY PARK, ILLING
					LCD8-14DH-L opper Lug - Two-Hole, Standard Barrel, 45° Angle Tong
0 7/02 S EV DATE	SAB		ASED RIPTION	10344	opportog 1440 holo, orangala bandi, 40 / highe forig