

4802, Plug, solder terminal, insulated, 3.5 mm, 3-pole, straight, UK-Connector



Description

- Solder terminal :
for cable mounting
- Data and Signal transfer
- Data and Signal Connectors 3-pole , insulated , straight

References


Alternative: Housing shielded [4802.1300](#)

Technical Data

Diameter	3.5 mm	Allowable Operation Temperature	-20°C to 70°C
Number of Poles	3-pole	Terminal	solder terminal
Ratings DC	1 A / 12VDC	Housings	insulated
Ratings AC	1 A / 12VAC	Style	straight
Dielectric Strength	500VDC	Lifetime	10000 Insertions
Insulation Resistance	> 10000 MΩ @ 500VDC		

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [General Product Information](#)

Dimensions



All Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Data and Signal Plug/Sockets	3.5	3-pole	solder terminal	4802.1310


Most Popular.

Availability for all products can be searched real-time: <http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging unit 100 Pcs

Mating Outlets/Connectors

Category / Description



[Data and Signal Plug/Socket Overview complete](#)

4802, Socket, solder terminal, screened, 3.5 mm, 3-pole, straight, UK-Connector	4802.2300
4802, Socket, solder terminal, insulated, 3.5 mm, 3-pole, straight, UK-Connector	4802.2310
4802, Socket, PCB terminals, screened, 3.5 mm, 3-pole, straight, UK-Connector	4802.2320
4802, Socket, PCB terminals, insulated, 3.5 mm, 3-pole, straight, UK-Connector	4802.2330

[Data and Signal Plug/Socket further types to 4802.1310](#)