

6

5

4

3

2

1

| MATERIAL NUMBER | OLD PART NUMBER |
|-----------------|-----------------|
| 130057-0001 | ENQAM315 |

| | |
|-----------------------|---------------|
| VOLTAGE RATING | 250 VAC/VDC |
| AMPERAGE RATING | 4 AMPS |
| PROTECTION | IP67 |
| OPERATING TEMPERATURE | -20°C TO 80°C |

| ITEM | COMPONENT | MATERIAL | FINISH |
|------|-----------------|---------------|------------------|
| 1 | CONTACT HOUSING | POLYCARBONATE | CLEAR |
| 2 | CONTACT PIN | COPPER ALLOY | GOLD OVER NICKEL |
| 3 | COUPLING NUT | ABS | BLACK |
| 4 | O-RING | VITON | BLACK |
| 5 | HOUSING | ABS | BLACK |

| | | |
|--|-------------|-----------------|
| RLSD DRAWING EC NO: WNA2009-0659 DRWN: BWOODMAN CHKD: JM APPR: JFMURPHY 2009/04/17 | 4/3/09 | 1 |
| | DESCRIPTION | QUALITY SYMBOLS |
| | | $\nabla=0$ |
| | | $\nabla C=0$ |
| A | REV | |

| GENERAL TOLERANCES (UNLESS SPECIFIED) | | |
|--|------------|-------------|
| | mm | INCH |
| 4 PLACES | $\pm .005$ | $\pm .0005$ |
| 3 PLACES | $\pm .005$ | $\pm .0005$ |
| 2 PLACES | $\pm .01$ | $\pm .001$ |
| 1 PLACE | ± 0.3 | $\pm .01$ |
| ANGULAR $\pm .5^\circ$ | | |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | |

| DIMENSION STYLE | | SCALE | DESIGN UNITS | THIRD ANGLE PROJECTION |
|-----------------|---|---------------------------------------|--------------|------------------------|
| IN/MM | | ---- | ---- | |
| DRAWN BY | DATE | TITLE | | |
| BW | 2009/04/03 | RJ-LNXX ATTACHABLE FOR STRANDED CABLE | | |
| CHECKED BY | DATE | ---- | | |
| TW | 2009/04/03 | MOLEX INCORPORATED | | |
| APPROVED BY | DATE | MATERIAL NO. | | |
| --- | --- | SD-130057-001 | | |
| SIZE | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | | |
| A | DOCUMENT NO. | | | SHEET NO. |
| | | | | 1 OF 1 |

| | | | | |
|--------------|--|---------------|-----------|--------|
| MATERIAL NO. | | SD-130057-001 | SHEET NO. | 1 OF 1 |
|--------------|--|---------------|-----------|--------|

6

5

4

3

2

1