

- Material**
- Terminal body
 - (contact pin): Brass(CuZn) Tin plated
 - Insulator (housing): Thermoplastic (UL94V-0) Green
- Electrical cULus**
- Voltage rating: 300VAC
 - Current rating: 20A
 - Wire range:
 - Solid wire(AWG):
 - Stranded wire(AWG):
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -30°C to +105°C
 - Soldering temperature: 245°C±10°C/5 Sec
 - Safety Approval: (cULus) pending


N=Number of contacts

RoHS compliant

Scale	1:1
TOLERANCE	
X.	±0.50
X.X	±0.30
X.XX	±0.10
DIM TOL	
X.°	±1°
Angle	TOL

①	Drawn	10.12.2009	Dean
	Modification	Date	Name

Date	Name	Customer-No.
10.12.2009	Dean	ASSMANN WSW-No. A-TB750-OQxxCV
10.12.2009	Hellwig	
Drawing-No.		ASS 3943 CO
Replace		rev01



Customer-No.	ASSMANN WSW-No.	ASS 3943 CO
ASSMANN WSW-No.	A-TB750-OQxxCV	rev01
Drawing-No.	ASS 3943 CO	rev01
Replace		Sheet